

RSSTM LTF

- patented -

TIMBER FRAME FASTENER

Star drive #30 applies approximately 650 lbf torque energy.

patented washer type head reinforced shoulder

Produces extreme pressure pulling the log down, eliminating the need to add a washer as required for common lag screws. Head can be countersunk 1" - 3" without pre-drilling a counter-sink hole.

case hardened steel

CLIMATEKTM coating, ACQ Approved. Lifetime limited warranty.

CEE Thread

Exclusive "CEE" Thread slightly enlarges hole for screw shank and allows log to settle without restriction.

Eliminates pre-drilling as required for the common lag screw. Complete and effective installation in one operation. For technical specifications see RSSTM Standards.

3/8" x 4" thread

Very sharp rolled threads, provide extreme pulling and withdrawal power.

patented W-Cut

Slices groove for next thread, reducing tension and pressure on fastener providing ease of installation.

Zip-TipTM

For quick and easy starting.

Bulk

UPC Code	Metric	U.S. Standard (Nominal Size)	Approx pcs /box	Approx pcs/lb
772691 91287 9	8.0 x 200	**3/8 x 8"	300	10
772691 91293 0	8.0 x 250	**3/8 x 10"	300	9
772691 91299 2	8.0 x 300	**3/8 x 12"	300	7
772691 91308 1	8.0 x 375	3/8 x 15"	300	6
772691 91321 0	8.0 x 460	3/8 x 18"	100	5
772691 91323 4	8.0 x 500	3/8 x 20"	100	5

See
Price
Index

Handy-Pak

UPC Code	Metric	U.S. Standard (Nominal Size)	pcs/box	Master Ctn Qty
772691 93287 7	8.0 x 200	**3/8 x 8"	50	n/a
772691 93293 8	8.0 x 250	**3/8 x 10"	50	n/a
772691 93299 0	8.0 x 300	**3/8 x 12"	50	n/a
772691 93308 9	8.0 x 375	3/8 x 15"	50	n/a
772691 93321 8	8.0 x 460	3/8 x 18"	25	n/a
772691 93323 2	8.0 x 500	3/8 x 20"	25	n/a

Diameter	#3/8	** #3/8	#3/8 recess change in progress. Check website or packaging for current bit size.
Bit Size	T-30	T-40	